



## PORTABLE GENERATORS

When a power outage occurs, when a disaster strikes, when you need power at a remote location, a portable generator guarantees you a source of electricity.

Portable generators are gas-powered machines that provide you with the power you need anywhere you are. Power outlets on the unit allow you to plug in extension cords, electric-powered tools, and appliances.

While many people buy a generator in the event of a power outage at their home or business, a portable generator allows you to bring power where none is available.

Generators have a range of capabilities based on starting watts and running watts.

Running watts refers to the continuous power a generator can supply, and starting watts refers to the momentary boost of power the generator can supply to start a motor.



## OVERVIEW

# SUA12000E

## PORTABLE GENERATOR

- 12,000 Starting Watts
- 9,000 Running Watts
- 2-Year Residential/1-Year Commercial
- 459cc/16hp OHV Engine
- 12V Multifunction Port; 1 - 12VDC 8.3A Adaptor Plug / USB Ready - new for 2017
- Full GFCI Outlets; 2 - NEMA 120VAC 20A, GFCI protected - new for 2017
- Electric Start
- Runs for 9 Hours at 50% Load
- Factory-Installed Handle
- Enough power for emergency use and more

### CONTACT US

10887 Commerce Way Unit A  
Fontana, CA 92337- 8240

[www.a-ipower.com](http://www.a-ipower.com)

**Phone:** 909-923-2068

**Fax:** 909-930-3719

**Email:** [support@a-ipower.com](mailto:support@a-ipower.com)

**Mon-Fri** 8 AM - 4:30 PM(PST)

Model	SUA12000E
UPC Code	851217006114
Running Watts	9,000
Starting Watts	12,000
Alternator	Senci
Automatic Voltage Regulator	Yes
AC Load	120/240V
Phase/ Frequency	Single/60Hz
Engine (OHV)	459cc/16hp
Starting Method	Electric Start
Lubrication	Splash
Low Oil Shutdown	Automatic
Running VAC Amperage	37.5A
LCD Hour Meter	Yes
Direct Circuit (DC)	Yes
Low Oil Alert Lamp	1
Circuit Breaker	8.3A, 20A, 30A, 38A
120V 20A NEMA 5-20R Outlet	4 GFCI
120V 30A NEMA L5-30R Outlet	1
120/240V 30A NEMA L14-30R Outlet	1
12V 8.3A Multifunction Port USB Ready	1
Weather Protected Outlet Cover	4
Neutral Bonded to Frame	Yes
Fuel Tank Capacity	7 gal. (25 L)
Run Time @ 50% Load	9 hours
Run Time @ 100% Load	7 hours
Built-in Gauge on Fuel Tank	Yes
Engine Oil Capacity (Qt. / L)	1.16 qt. (1.1 L)
Recommended Oil	SAE 10W-30
Muffler with USDA Spark Arrester	Yes
Noise Level, dBA at 23 ft. (7m)	78
Durable Tubular Steel Frame	1.25 in diameter (32 mm)
Fold-Down Handle	Factory Built-in
Maintenance Free Battery	12V/14AH
Engine Oil Supplied	1.0 qt. 10W-30
DC Charging Cable	1
Spark Plug Socket	Yes
Wheel Kits	9.5-in. solid wheel
Gross Weight	222 lbs./98 kgs
Net Weight	216 lbs./93.5 kgs
Assembly Dimension	27.6 x 27.2 x 25.6 in.
Packing Dimension	28.5 x 21.6 x 24 in.
Warranty	2-Year Residential/1-Year Commercial
Emission Certification	EPA