



EFI
ELECTRONIC FUEL INJECTION
EQUIPPED

95%

95% REDUCTION IN CARBON MONOXIDE EMISSIONS*

25%

25% FUEL SAVINGS*

40%

40% LOWER COST OF OWNERSHIP*

10kW

**INDUSTRY FIRST:
10kW FROM 459cc ENGINE**



ALL NEW FOR 2019 – **EFI PRECISION & POWER**

A-iPower introduces an all new electronic fuel injected portable generator. This unit is designed for ease of use with power on demand - not found on other generators with same sized carbureted engines.

Our SUA13000EFI offers a full enclosed EFI system that offers a buyer many benefits:

- Vastly reduced emissions
- Automatic altitude sensing technology
- Longer run times / greatly increased fuel efficiency
- Decreased operating costs
- First 10kW+ portable generator from 459cc engine
- Easier starting compared to carbureted generators
- Superior throttle response across entire RPM range
- Enhanced internal & external engine features

BRAND NEW DESIGN FOR 2019



- 13,000 Starting Watts – 10,000 Running Watts
- Warranty: 2-Year Residential
- 459cc, OHV, 4-Cycle, HD EFI Engine
- 69 dBA – for Super Quiet Operation
- 4% or Less THD - Safe Power for Sensitive Electronics
- EPA / CARB / EPAIII
- Portability Kit Included

Inclusions: SUA13000EFI



CONTACT US

10887 Commerce Way, Unit A
Fontana, CA 92337 USA

www.a-ipower.com

Phone: 909-923-2068

Fax: 909-930-3719

Email: support@a-ipower.com

Mon-Fri 8 AM - 4:30 PM(PST)

ELECTRONIC FUEL INJECTED GENERATOR

Model#	SUA13000EFI
Rated Voltage & Frequency	120V/240V / 60Hz
Running VAC Amperage	35.4A
Rated Output	10000W ±5%
Max. Output	13000W
Alternator Brand	Senci
Automatic Voltage Regulator	Single Phase- 7kW/312038
Engine Brand	Senci SC460
Engine Type	OHV, 4-Stroke HD
Engine Displacement	459cc
Bore X Stroke (mm)	92*69 mm
Engine RPM	3600
AC Load	100%
Phase	Single
Recommended Oil	SAE 10W-30
Lubrication Method	Splash Sump
Choke Type	Manual
Fuel Tank - Gasoline	6.6 Gal / 25 L
Fuel Gauge	Yes
Starting Method	Electric Start & Recoil Back-Up
Low Oil Shutdown	Yes
Oil Volume	1.2 Qt / 1.1L
Low Oil Alert Light	Yes
Compression Ratio	8.5:1
Ignition Type	Transistorized Ignition
Full Load Run Time - Gas	5 Hours
1/2 Load Run Time - Gas	8.5 Hours
LCD Hour Meter	Yes
DC Volts	12V 8A
Weather Protection on Outlets	Yes
Circuit Breaker	Yes
Muffler, Spark Arrestor	Yes
Frame Thickness	φ32X1.2mm
Handle and wheels	Yes
Battery	Lead Acid - 12V, 21Ah/UL/CE
Noise Level: dBA at 23 ft / 7 m	69dBA Sound Rating (1/4 Load)
THD	5%
Emissions	EPA3
Net Weight	218 Lbs / 99 Kg
Gross Weight	224 Lbs / 101 Kg
Assembly Dimensions (L*W*H)(in./mm)	27.95 x 21 x22.8in / 710 x 535 x 580 mm
Receptacle Details (Type and rated amps)	
Accessories included	Oil, charging cables, sparkplug tool, manual, Quick Start Guide