



PORTABLE GENERATORS

When a power outage occurs, when a disaster strikes, when you need power at a remote location, a portable generator guarantees you a source of electricity.

Portable generators are gas-powered machines that provide you with the power you need anywhere you are. Power outlets on the unit allow you to plug in extension cords, electric-powered tools, and appliances.

While many people buy a generator in the event of a power outage at their home or business, a portable generator allows you to bring power where none is available.

Generators have a range of capabilities based on starting watts and running watts.

Running watts refers to the continuous power a generator can supply, and starting watts refers to the momentary boost of power the generator can supply to start a motor.



OVERVIEW

SUA4500

PORTABLE GENERATOR

- 4,500 Starting Watts
- 3,500 Running Watts
- 2-Year Residential/1-Year Commercial
- 208cc/7HP OHV Engine
- 30 Amp RV Adapter
- Easy-Pull Recoil Start
- Average run time of 11 hours at 50% load
- Factory-Installed Handle
- Perfect size for tailgating, camping, power tools, and more.

CONTACT US

10887 Commerce Way Unit A
Fontana, CA 92337- 8240

www.a-ipower.com

Phone: 909-923-2068

Fax: 909-930-3719

Email: support@a-ipower.com

Mon-Fri 8 AM - 4:30 PM(PST)

Model	SUA4500
UPC Code	851217006077
Running Watts	3,500
Starting Watts	4,500
Alternator	Senci
Automatic Voltage Regulator	Yes
AC Load	120/240V
Phase/ Frequency	Single/60Hz
Engine (OHV)	208cc/7hp
Starting Method	Manual
Lubrication	Splash
Low Oil Shutdown	Automatic
Running VAC Amperage	14.6A/29.1A
Starting VAC Amperage	18.7A/37.5A
LCD Hour Meter	Yes
Direct Circuit (DC)	Yes
Low Oil Alert Lamp	1
Circuit Breaker	15A, 30A
120V 20A NEMA 5-20R Outlet	4
120/240V 30A NEMA L14-30R Outlet	1
Voltage Selector Switch	Yes
Weather Protected Outlet Cover	3
Neutral Bonded to Frame	Yes
Fuel Tank Capacity	4 gal. (15 L)
Run Time @ 50% Load	11 hours
Run Time @ 100% Load	7.5 hours
Built in Fuel Gauge	Yes
Engine Oil Capacity (Qt. / L)	0.63 qt. (0.6L)
Recommended Oil	SAE 10W-30
Muffler with USDA Spark Arrester	Yes
Noise Level, dBA at 23 ft. (7m)	68
Durable Tubular Steel Frame	1 in. diameter (25 mm)
Fold-Down Handle	Factory Built-in
Engine Oil Supplied	0.6 qt. 10W-30
RV Adaptor	Yes
Spark Plug Socket	Yes
Wheel Kits	7-in. solid wheel
Gross Weight	117 lbs. / 51 kgs
Net Weight	111 lbs. / 48 kgs
Assembly Dimension	24.5 x 22.8 x 22.6 in.
Packing Dimension	24.4 x 19.1 x 21 in.
Warranty	2-Year Residential/1-Year Commercial
Emission Certification	EPA