



## PORTABLE GENERATORS

When a power outage occurs, when a disaster strikes, when you need power at a remote location, a portable generator guarantees you a source of electricity.

Portable generators are gas-powered machines that provide you with the power you need anywhere you are. Power outlets on the unit allow you to plug in extension cords, electric-powered tools, and appliances.

While many people buy a generator in the event of a power outage at their home or business, a portable generator allows you to bring power where none is available.

Generators have a range of capabilities based on starting watts and running watts.

Running watts refers to the continuous power a generator can supply, and starting watts refers to the momentary boost of power the generator can supply to start a motor.



## OVERVIEW

# SUA5000

### PORTABLE GENERATOR

- 5,000 Starting Watts
- 4,250 Running Watts
- 2-Year Residential/1-Year Commercial
- 223cc/7.5hp OHV Engine
- 12V Multifunction Port; 1 - 12VDC 8.3A Adaptor Plug / USB Ready - new for 2017
- Full GFCI Outlets; 2 - NEMA 120VAC 20A, GFCI protected - new for 2017
- Easy-Pull Recoil Start
- Average run time of 9 hours at 50% load
- Factory-Installed Handle

### CONTACT US

10887 Commerce Way Unit A  
Fontana, CA 92337- 8240

[www.a-ipower.com](http://www.a-ipower.com)

**Phone:** 909-923-2068

**Fax:** 909-930-3719

**Email:** [support@a-ipower.com](mailto:support@a-ipower.com)

**Mon-Fri** 8 AM - 4:30 PM(PST)

Model	SUA5000
UPC Code	851217006084
Running Watts	4,250
Starting Watts	5,000
Alternator	Senci
Automatic Voltage Regulator	Yes
AC Load	120/240V
Engine (OHV)	223cc/7.5hp
Starting Method	Manual
Lubrication	Splash
Low Oil Shutdown	Automatic
Running VAC Amperage	17.7A
LCD Hour Meter	Yes
Direct Circuit (DC)	Yes
Low Oil Alert Lamp	1
Circuit Breaker	8.3A, 20A, 30A
120V 20A NEMA 5-20R Outlet	2 GFCI
120V 30A NEMA L5-30R Outlet	1
120/240V 30A NEMA L14-30R Outlet	1
12V 8.3A Multifunction Port USB Ready	1
Weather Protected Outlet Cover	3
Neutral Bonded to Frame	Yes
Fuel Tank Capacity	4 gal. (15 L)
Run Time @ 50% Load	9 hours
Run Time @ 100% Load	6 hours
Built-in Gauge on Fuel Tank	Yes
Engine Oil Capacity (Qt. / L)	0.6 Qt. (0.6L)
Recommended Oil	SAE 10W-30
Muffler with USDA Spark Arrester	Yes
Noise Level, dBA at 23 ft. (7m)	68
Durable Tubular Steel Frame	1 in. diameter (25 mm)
Fold-Down Handle	Factory Built-in
Engine Oil Supplied	0.6 qt. 10W-30
DC Charging Cable	1
RV Adaptor	1
Spark Plug Socket	Yes
Wheel Kits	7-in. solid wheel
Gross Weight	130 lbs./59 kgs
Net Weight	123 lbs. / 54kgs
Assembly Dimension	24.4 x 22.8 x 22.6 in.
Packing Dimension	25.4 x19 x 21.6 in.
Warranty	2-Year Residential/1-Year Commercial
Emission Certification	EPA